

Professional Chemical Solutions

For Mould's Problems

緑色長期模具防銹劑 Mould Protector(Green)


模具清洗劑(快幹及慢幹) Mould Cleaner I & II

獨特的不傷塑料配方能快速去除模具表面之油漬及 碳化物,使模具在注塑時不受到油的污染,當清洗滲 進模具配件間隙時對密封件也不會傷害.慢幹配方 更爲一般需要表面處理而設,不會受到因溶劑快幹

Mould Cleaner I & II, (Fast and Slow dry), this mould cleaner was produced by our special ingredient which is harmless to plastic and rubber materials and actively remove oily surface or impurities. The slow dry formula is special designed for those need to rub the surface and "free time" to adjust individual requirement











高純度化學合成防銹層,獨特于模具在下次使用時不需使用任何清洗劑除油 都可在首幾次注塑時自然脫離模具,防銹層還可在室内任何環境下保護模具

This mould protector wax based is designed to forms a complete wax-like protective film over the surface of moulds and dies. It's prevents surface contamination on start-up from dissolved deposits between inserts, ejector pins, etc. Its "self-clean" through plastic injection process therefore save cost and time when reuse the mould.





EDM SUPER

特别之低黏度可提高期加工電蝕時之冲屑度,透明清澈配方更可使能見度 增加,ROHS及MSDS可再一認定對手及人體的傷害,EDM SUPER 還可混合研磨粉加强放電速度及表面光潔度,除了銅工外還可用于石墨放電,

EDM Super is a low viscosity, highly transparent and ROHS qualified product. It is harmless to human and environment friendly. EDM Super could mix with conductive grinding powder or graphite powder to improve the brightness and conductivity.









特别的高黏度配方可使絲攻充份得到保護,同時高黏度的拉絲效果更可使退 攻時使停留在孔内的金屬削黏付于絲攻上使得孔内順滑,銅及鋁的攻牙油配 方更是對其材料不會產生腐蝕外還可提供保護.推薦用于手攻絲錐及機攻絲

This is special formulated by VI additive to easy remove the impurities during "tapping" process, Whereby it is protected the "tapping tool" as well. We have tapping oil which is special for tapping on aluminium & copper materials without corrosive into that materials. This tapping oil is suaitable for "hands-tap" or machine tapping.

模具免燒焊修補泥膠 Mould Repair Clay

高强度的特别配方使泥膠可在三小時内形成比 718還要硬的材料,推薦用于模具運水破裂,模具表 面沙眼,模具破裂,倒塞運水孔,孔内螺絲紋重做及因 孔隙開大後需變小的用途,代替傳統燒氦焊之煩惱.

Mould Repair Clay is a clay act effectively to repair "sand holes", mould crack, leakages in cooling pipes. After 3 hours fully harden, it's equal to hardness as 718 steel materials. Its can be "tapping", grinding and sand blasting. It can replace "traditional welding" Method.



專業水性切削液

發臭,傷手,刀具損耗及生銹都是 CNC加工中心或車床冷却的問題 ,FUKKOL水性切削油系列有一整套完 善解决方案及針對不同物料而設的冷 却液,更可使用機械的轉速及材料的硬 度而計算出所需的冷却程度

Unpleasant smell hands irritated wear and tear to cutting tools, rust on metal is the common problems faced by CNC engineering department. Due to this reason, FUKKOL has created a full system to counter these problems and adjust the formula according to materials, rotation of machine, hardness of metal. Therefore, we can calculate the accurate "cooling effect" for specify needs.



獨有的陽離子配方會直接興銹蝕而產生反應,從而使金屬銹蝕 表面快速分離,因此不會做成金屬因銹蝕而出現的尺寸差距 .中性水基的不傷手配方更添安全及環保

Rust Remover

FUKKOL

DAC 2, formulated based on +/- ion chemicals interaction. It will act effectively to remove rust without corrosive to metal surface and harmless to human and environmental friendly.





HT Paste (Mould Parts Protective Pas

-種獨有的超耐高温配方,解决多年來模具配件因磨擦及模具配件太 情密而緊蝕所導致燒的問題,大大减少模具配件更换時間,提高效率 每次使用後可維持3年,特别適合用于模具司筒,頂針,鑲件及導軌.

HT paste is a paste formulated by anti-wear and anti-heat additives. It's contains Nano ceramic powder which can stands 1400°C. It does prevent "burning" in the mould therefore reduce the workload to exchange and reassemble the mould parts

Hong Kong Head Office:

Kalen Internation Ltd.

Room 1, 6/F, New Treasure Center, 10 Ng Fong Street, San Po Kong, Kowloon, Hong Kong

TEL: 0852-24202444 (Line 3) FAX: 0852-24851418

Malaysia Offices:

Fukkol Holdings (M) Sdn Bhd.

Sub Lot 16, lot 772, Jin Subang 4, Tmn Perindustrian Sg. Penaga,47610,Subang Jaya,Malaysia.

TEL: +603 56217290 Fax: +603 56217293

China Factory & office:

Kalen Lubricants Techology (Hui Zhou) Ltd.

Tie Chang Precinct Shi Wan Town Bo Luo County

Hui Zhou City, Guang Dong, China

TEL: 086 752 6616270 (Line 10) FAX: 086 752 6616269

www.fukkol-lube.com

MALAYSIA 2009's Courses: Training On Plastic Injection Defects
Analysis and Troubleshooting Q&A.....Coming Soon