



TEEHNICAL DATA SHEET



FUKKOL COLORLESS CORROSION INHIBITOR



Brief introduction:

The high transparent anticorrosion agent is designed for the corrosion protection requirements on the mold. Its unique transparent soft film has the function of fast film forming and strong penetration, and it also ensures that it will not outflow and stay in the process.

Purpose:

- Used for outdoor storage of steel materials and machinery.
- used for rust prevention of parts during processing, storage and transportation.
- used for corrosion protection of iron materials, equipment, machinery and so on in factories, houses and garages in coastal areas.
- long term rust prevention for stamping metal dies and so on.

Performance characteristics:

- semi dry, hard, dry, touch will not make the outer layer of anticorrosive agent stripped.
- Outdoor air, salt, chemical or corrosive atmosphere or harsh conditions, can play an excellent anti rust power.
- It is most suitable for long term rust prevention in indoor and outdoor.
- It has penetrability and can be used to rust the outer parts of the tiny parts.

Products Code	Packings	Capacity
I99281-500ML	Can.	500ML
I99281-18L	Pail	18L
I99281-200L	Dum.	200L

Usage method:

Apply to the parts directly and evenly before shaking.

Typical Physical Properties:

Product	FUKKOL COLORLESS CORROSION INHIBITOR	
Appearance	Transparent yellow liquid	
Density 25°C, g/cm³	0. 65–0. 75	
Copper corrosion 100℃ 3h	la	
Antirust time	1-2 years (indoors)	





TECHNICAL DATA SHEET

Water solubility

Insoluble in water

Matters needing attention:

- 1. pressure vessels, avoid direct sunlight, stored at below 50 degrees Celsius.
- 2. should not be sprayed to the flame. Do not stamp or burn the container.