




FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET

SUPERMAX 3 SYNTHETIC CUTTING OIL



Description:

SUPERMAX 3 SYNTHETIC CUTTING OIL Anti atomization, chlorine free, active sulfur cutting fluid, suitable for medium to heavy machining. The content of high-efficiency fat oil can meet the requirements of different metals and different kinds of machining, especially for the occasions where the cutting oil can not contain chlorine.

Products Code	Packings	Capacity
I120124-4L	Can	4L
I120124-18L	Pail	18L
I120124-200L	Durm	200L

Purpose :

It is suitable for the most difficult cutting operation. It can be used in stainless steel, tensile steel and other metals.

It is suitable for various processes such as cutting, tower teeth, drilling, punching and shearing, stretching and so on.

Performance characteristics :

- It has excellent anti smog performance and low volatilization characteristics, which can provide the best operating environment and the most economical loss.
- excellent extrusion performance, reduce heating during machining and reduce tool wear.
- Good cooling and lubrication properties can extend the service life of the tool.

Typical physical properties

DENSITY g/cm ³	FLASH POINT °C	POUR POINT °C	VISCOSITY 40°C	Appearance
0.82~0.85	>200	<-9	28~34	Yellow transparent liquid

Matters needing attention:



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET

1. Pay attention to sealing and preserving oil products