



TECHNICAL DATA SHEET

LAYOUT INK SPRAY BLUE





Description:

Marking Ink Spray-Blue is a specialised paint designed for the marking out of metal surfaces in Toolrooms, Machine shops etc. The thin, dry film enables clear, sharply defined lines to be scribed on most surfaces without flaking. Marking Ink Spray-Blue is designed for use on bright or machined surfaces.

Features:

- · Allows clear, sharp definitions.
- Will not chip or flake.
- · Resists wash off, ie. Water mix cutting fluids.
- · Easy to apply and remove.

Directions for Use:

- Layout Ink Spray Blue should be applied to a grease/dirt free surface.
- Shake well, hold upright and spray from a distance of 15-25cm (6-8ins).
- Allow film to dry for a minimum of 2 minutes before use. Ensure adequate ventilation.





TECHNICAL DATA SHEET

N.B. To avoid blockage, clear spray head after use by inverting can and depressing button for 2-3 seconds until jet is cleared.

Layout Ink Spray Blue can be easily removed with the use of a suitable solvent – FUKKOL Crackcheck Cleaner



Technical Data:

Appearance : Dark blue, dry film

Propellant : Butane/Propane

Solvent : Acetone

Flash point : < 0c

Storage: temperature should be kept below 50°C. Storage area should be out of direct sunlight.

Pack sizes and Part Codes:

500ml

Part Code: 36670

Health and Safety:

Safety data sheet is available from the Customer Service Department,