



**FUKKOL**

**Nourishment for**  
Your Machines

# TECHNICAL DATA SHEET

## Spindura oil

ISO 2、 5、 7、 10、 15、 22



Description:

- High quality, antioxidant and antirust spindle oil.
- High speed bearing lubricating oil.
- Low viscosity hydraulic oil.

Purpose :

- Low viscosity is suitable for high speed machinery.
- Excellent wear resistance.
- It has antirust and anticorrosion effects.
- Excellent oxidation stability prevents formation of colloid and sludge.
- The color is so shallow that it will not leave dark oil stains on the fibers.
- High viscosity index and narrow volatile range reduce the formation of oil mist.
- Good separation characteristics of water and oil.

Products Code	Packings	Capacity
I100084-4L	Can	4L
I100084-18L	Pail	18L
I100084-200L	Durm	200L

Performance characteristics :

- High speed mechanical lubricants are especially suitable for lubrication of knitting machines and spindles of spinning machines.
- High speed bearings, such as tool rotating shafts, especially grinders.
- High speed bearings, such as tool rotating shafts, especially grinders.

Typical Physical Properties:

ISO Grade	Appearance	DENSITY 20 °C , g/cm <sup>3</sup>	FLASH POINT °C	POUR POINT °C	VISCOSITY 40°C mm <sup>2</sup> /s	COPPER CORROSION 100 °C, 3 hrs
2	Light yellow transparent	0.80-0.83	>120	<-9	1.98-2.42	1a



**FUKKOL**

**Nourishment for**  
**Your Machines**

# TECHNICAL DATA SHEET

	liquid					
5	Light yellow transparent liquid	0.82-0.85	>130	<-9	4.14-5.06	1a
7	Light yellow transparent liquid	0.82-0.85	>140	<-9	6.12-7.48	1a
10	Light yellow transparent liquid	0.82-0.85	>140	<-9	9-11	1a
15	Light yellow transparent liquid	0.82-0.85	>140	<-9	13.5-16.5	1a
22	Light yellow transparent liquid	0.82-0.85	>160	<-9	19.8-24.2	1a