



**FUKKOL**

**Nourishment for**  
**Your Machines**

# TECHNICAL DATA SHEET

## RUSTKING S1



### Description:

High and multi-purpose antirust agent is made from high melting point wax paste and special rust inhibitor additive with permeability and water displacement capacity.

| Products Code  | Packings | Capacity |
|----------------|----------|----------|
| I100138-1-4L   | Can      | 4L       |
| I100138-1-18L  | Pail     | 18L      |
| I100138-1-200L | Durm     | 200L     |

### Purpose :

It is mainly used for the protection of iron and steel objects. Direct exposure before, during or after processing.

Outdoor steel objects, transportation undercoat, transformer shell, bridge and floating bucket, storage tank, pressure box, gas holder, lifting appliances, farm implements.

### Performance characteristics :

- No gasification solvent, so it meets the requirements of environmental protection.
- No smelling smell, suitable for general workshops.
- Special protective film is produced to prevent rust on the metal surface, and the indoor antirust period can last up to 1-2 years.

### Typical Physical Properties:

|                                |                    |
|--------------------------------|--------------------|
| An unvolatile component %,     | Not greater than15 |
| Oil film species, Tilm Type    | Thin film          |
| Density 25℃, g/cm <sup>3</sup> | 0.65-0.7           |
| Flash Point PMC ° C            | -12                |
| Indoor Protection              | 1-2 years          |
| Copper corrosion50℃ 3h         | ≤1b                |

### Matters needing attention:

- 1, This product contains volatile components, pay attention to seal preservation of oil products.
- 2, This product is flammable, do not contact with open fire