



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET

ANTI-RUST SERIES FUKKOL RUSTER WAX



Description :

High white medium antirust agent is a multi-purpose antirust agent. It is suitable for gear, bearings, fasteners and other parts and facilities, including moulds, sliding parts, and other exposed surfaces stored in indoor equipment for general corrosion protection.

Application :

Antirust sprays are ideal for rust protection of machined parts exposed to metal surfaces and storage, transportation and working procedures. The dry protective film produced by the antirust sprayed spray is automatically removed during the injection process, and there is no need to clean the parts after processing or using. This product is packed in a convenient aerosol tank and is the ideal antirust agent in the workshop.

Products Code	Packings	Capacity
I56686-500ML	Can.	500ML
I56686-18L	Pail	18L
I56686-200L	Dum.	200L

Performance Characteristics :

- Excellent indoor seal corrosion protection.
- Produce a soft protective film.
- Generally, the surface of the components need not be degreased.
- It has good protection in wet environment.
- Aerosol tank packaging, easy to use.
- Fluorine free

Typical Physical Properties :

APPEARANCE	ODOR	FLASH POINT °C	COPPER CORROSION 100 °C, 3 hrs	ANTIRUST PERIOD Yrs Room Temperature	DENSITY 25 °C , g/cm ³
White Liquid	Solvent odor	<-18	1a	3	0.75~0.8