



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET

Molyfu spray



Description:

FUKKOL Molybdenum disulfide antiwear agent, Special reinforced molybdenum disulfide powder, Effectively reducing metal friction and improving working load.

FUKKOL Molybdenum disulfide antiwear agent can be used in metal, Rubber and areas requiring dry lubrication. The unique dry powder can effectively protect the metal surface from oil pollution. Make it increase the use cycle of the product, The product has good anti chemical and water resistance, Therefore, it can be considered in some harsh environments, Suitable for working environment within 400 C.

Purpose:

It is recommended to use the gasket, Conveyer belt and bearing. Automatic and manual mechanical equipment for motor equipment, Or can be used for gears and guideways, Lubrication of most sliding mechanical parts in cam and regulating valves.

Performance characteristics:

- Anti wear and wear resistance
- Dustproof, ash proof and anti pollution
- Can dissolve with other different kinds of lubricating oil

Products Code	Packings	Capacity
I66466-500ML	Can.	500ML
I66466-18L	Pail	18L
I66466-200L	Dum.	200L

Typical physical properties

Product	66466 Molyfu spray
Appearance	Gray black liquid
Density 25°C, g/cm ³	0.721
Copper corrosion 100°C 3h	1a
Water solubility	Insoluble in water
Propellant	LPG

Matters needing attention:

1. Pressure vessel, Avoid direct sunlight, Place at a place below 45 degrees Celsius.
2. It should not be sprayed to the flame. Do not stamp or burn the container.
3. This product flammable.