



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET



Leak detector spray



Description:

High gas leak detection spray is a specially manufactured liquid. It is specially designed to measure extremely fine gas leaks. A thin, homogeneous film is formed after spraying the high gas leakage spray because the surface active additive can accurately point out any gas leakage or leakage at the joint.

Purpose:

It is applicable to the following general industrial gases: compressed gases, acetylene, butane / propane, hydrogen, natural gas and city gas.

Performance characteristics:

- for most of the gas
- spray tank packaging is easy to use and fast
- convenient and precise use in some unapproachable places.
- no waste or spillover

Products Code	Packings	Capacity
I103061-500ML	Can.	500ML
I103061-18L	Pail	18L
I103061-200L	Dum.	200L

Usage method:

Shake well before use and spray 25 to 30 centimeters from target. If the film is sprayed, foam leakage can be identified. Compatibility tests should be done before painting or covering surfaces, plastics and rubber.

Typical physical properties :

Product	03061 Leak detector spray
Appearance	Colorless clear transparent liquid
Density 25°C, g/cm ³	0.945
PH VALUE	7.5-9
Water solubility	Dissolve in water



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET

Propellant

Dimethyl ether

Matters needing attention

1. pressure vessels, avoid direct sunlight, stored at below 50 degrees Celsius.
2. should not be sprayed to the flame. Do not stamp or burn the container.
3. this product is flammable.