



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET

X-CUT 15CHORING FREE LOW VISCOSITY CUTTING OIL



200L

18L

4L

Description:

FUKKOL X-CUT 15CHORING FREE LOW VISCOSITY CUTTING OIL It is a transparent light yellow, anti-atomization, chlorine-free, thioester-free cutting oil series, suitable for medium to heavy machinery processing. This product has many extreme pressure and viscosity levels, and the content of fat oil is different. It can meet the requirements of different metals and different kinds of mechanical processing, especially when chlorine is not in contact with or chlorine-containing cutting oil is not used.

Purpose :

It is used for machining and grinding of copper and iron and die steel.

Products Code	Packings	Capacity
I120123-4L	Can	4L
I120123-18L	Pail	18L
I120123-200L	Durm	200L

Performance characteristics :

- Good lubricity and extreme pressure
- improve surface finish
- no chlorine, sulfur.

Typical Physical Properties

Model	DENSITY g/cm ³	Flash point °C	VISCOSITY 40°C	Appearance
X-CUT 15	0.85~0.95	≥170	28.8~35.2	Pale yellow liquid

Matters needing attention:

1. Pay attention to sealing and preserving oil products



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET