



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET

BLUE PRESSURE GREASE 0,1,2



Description:

FUKKOL Sapphire high speed extreme pressure grease is a grease NLGI 2 made of compound calcium as thickener. Smooth structure and excellent adhesion, Anti water flushing and sputtering. Because of this grease, it has the function of antirust and wear proof, A vehicle used to operate on a road or site, And the spindle pin of a heavy vehicle with a towing frame, Universal joint and bucket door pin Most effective. Adjust and lubricate the machine operation process.

Purpose:

It is used for all kinds of buses, trucks, minivans, buses, agricultural tractors and buildings. Ball sockets for chassis, wheel bearings, clutch bearings, steering and suspension systems such as machinery. Joint and universal joint, etc. The suitable temperature range for continuous running time is $-20^{\circ}\text{C} \sim 200^{\circ}\text{C}$.

Products Code	Packings	Capacity
I100292-4L	Can	4L
I100292-18L	Pail	18L
I100292-200L	Durm	200L

Performance characteristics:

- Multi purpose grease can provide anti abrasion, heat and water washing performance under impact and heavy load operation.

Typical physical properties:

BLUE PRESSURE GREASE	NLGI	Coning 1/4	Drop point $^{\circ}\text{C}$	Appearance
Grease 0	0	88~97	>180	Blue ointment
Grease 1	1	76~85	>220	Blue ointment
Grease 2	2	64~74	>240	Blue ointment

Matters needing attention:

1. Please use it in a suitable temperature range, so as not to cause the grease to freeze or melt.
2. Sealed storage.