



®

FUKKOL**Nourishment for****Your Machines**

TECHNICAL DATA SHEET



5 in 1 Freeze & Dismantle



Description:

The high freeze screw loosening agent uses instantaneous freezing to cause the components to shrink, and the instant freezing at -40 C can help quickly and effectively loosening the bitten and corroded screws. The resulting rust layer cracks guarantee the penetration of the product's lubricating components; the special formulation of the lubricating oil is designed to allow the lubricating components to penetrate rapidly into the rust layer; after the screw is loose, the components will be lubricated and protected from corrosion. .

Purpose:

It is used to solve the occlusal and corrosion problems of screw and cylindrical components in all industries, including cars, trucks, farm and construction machinery, and general industry.

Products Code	Packings	Capacity
I88679-500ML	Can.	500ML
I88679-18L	Pail	18L
I88679-200L	Dum.	200L

Performance characteristics:

- Instant freezer (40 degrees below 7 seconds)
- Ensure that the nuts and bolts will not cause deformation, distortion and slip angle due to excessive force loosening screws.
- Save the time and money for loose screws.
- 5 in one special lubricating oil with quick freezing, penetration, rust, rust and lubrication.

Typical physical properties

Product	5 in 1 Freeze & Dismantle
Appearance	Water clear
Density 25°C, g/cm ³	0.68
Copper corrosion 100°C 3h	1a
Water solubility	Insoluble in water
Propellant	Hydrocarbon

Matters needing attention

1. pressure vessels, avoid direct sunlight, stored at below 50 degrees Celsius.
2. should not be sprayed to the flame. Do not stamp or burn the container.