



®

**FUKKOL**

**Nourishment for**  
**Your Machines**

# TECHNICAL DATA SHEET

## MOULD RELEASE SERIES

### FUKKOL MOULD RELEASE AGENT (PAINTABLE)



#### Description:

The high dry release agent is a spray release agent, which provides fast speed for most plastic and rubber products molded by injection moulds. Czechoslovakia, effective and uncontaminated, high dry stripping agent is specially developed for some products that need to be carried out in incidental process, such as printing, paint, electroplating, hot stamping and pressing welding, which require no "silicone problem".

#### Precautions:

Pressure vessels, avoid direct sunlight, stored at temperatures below 50 degrees.

Do not stamp or burn the container.

It should not be sprayed to the surface of a flame or incandescent metal.

Inflammable Materials.

Products Code	Packings	Capacity
I11881-500ML	Can.	500ML
I11881-18L	Pail.	18L
I11881-200L	Dum.	200L

#### Performance Characteristics:

- Hyperfine injection makes the whole die fully covered
- Increase the degree of smoothness and reduce the risk of overspraying
- Reduce the problems caused by marking and transportation, quick and effective demoulding and economic benefits. It can be demolde many times with only one spray.
- The highly effective and durable lubricating film can provide multiple demoulding, better than other silicone formulations.
- Little environmental impact, no chlorinated fluorocarbon (CFC) propellant.
- Suitable for all kinds of thermoplastic materials, especially ABS and PS.
- It does not affect the incidental operation.

#### Typical Physical Properties:

APPEARANCE	ODOR	FLASH POINT °C	BOILING POINT °C	VOLATLLE %	DENSITY 25 °C , g/cm <sup>3</sup>
Water clear	Solvent odor	-3	25~35	95.5~97.5	0.65~0.70