



**FUKKOL**

**Nourishment for**  
**Your Machines**

# TECHNICAL DATA SHEET

## Painto lic paint remover



### Description:

It is easy to operate at normal temperature and is easy to operate. It has no flammability and fast painting speed. It is widely used in metal coating. After the metal surface coating is removed, there is no corrosion on the metal surface and the problem of discoloration lamp

appears.

Products Code	Packings	Capacity
I100079-4L	Can	4L
I100079-18L	Pail	18L
I100079-200L	Durm	200L

### Purpose:

Use the original fluid to immerse the workpiece. After the film is off, remove it from the steel ball or towel. The soaking time depends on the thickness of the coating. For the first time or for lack of experience, it is necessary to try a small amount of trial and then use it in large quantities.

### Performance characteristics:

- Easy to use and simple
- lacquer speed

### Typical Physical Properties :

Painto lic Paint remover	Relative density g/cm <sup>3</sup>	Smell	Appearance
—	1.01	Irritant smell	Colorless liquid

### Matters needing attention :

- 1.This product is irritating and toxic. Therefore, it is necessary to wear protective clothing (gloves and respirators) during operation.
2. Do not let children contact, do not drink.
- 3.Seal in a cool and ventilated place, and do a good job of "dangerous goods do not move" wakeup target, strictly



**FUKKOL**

**Nourishment for**  
**Your Machines**

# TECHNICAL DATA SHEET

prohibited in the sun exposure.